

AIR-COOLED AFTERCOOLER



Model No	:AAC 850
Air capacity	:1445m ³ /hour (850cfm)
Air inlet temperature	:80 deg C
Air outlet temperature	:10 deg C above ambient
Safe working pressure	:150 psi (10.34 bar)
Air-driven motor	:5 Hp
Inlet manifold	:1 port x 2"
Outlet manifold	:2 ports x 1-1/2" c/w 1-1/4" ballvalves 2 ports x 3/4" c/w ballvalves
Standard Accessories (fitted in Aftercooler)	:Pressure gauge, safety relief valve, 2" moisture separator with drain valve, air filter, regulator & lubricator assy.
Cooler material	:Copper alloy tubes / aluminun fins
Dimension	:1163mm (W) 800mm (D) 1531mm (H)
Weight	:220 kg

TTL Sales And Rental Sdn Bhd
No. 18, Jalan Nouvelle, Nouvelle Industrial Park Balakong, Jalan Perindustrian Balakong,
43300 Seri Kembangan, Selangor Darul Ehsan, Malaysia.
Phone : +6019-987 4168 Fax : +603-8955 4466
Email : enquire@ttl-holdings.com

Note: Product data contained in this catalogue is to be used for reference purposes only.

TTL Sales and Rental Sdn Bhd reserves the right to modify or improve product technical specifications at any time.

Before using this Product, read all Instructions, Literatures, Specifications, Labels and Warnings either send with or affixed to the Product.